

Recommended PCB Soldering Pattern

_	Dimensions						
Туре	A	В	С	D	b	С	
A1(1.0)	0.75	1.02	8.5	1.0	1.20	8.5	
A1(1.3)	0.75	1.02	8.5	1.3	1.20	8.5	
A1(1.7)	0.75	1.02	8.5	1.7	1.20	8.5	
A2(2.1)	8.0	1.02	8.5	2.1	1.20	8.5	
A4(0.8)	0.8	1.02	8.5	0.8	1.20	8.5	
A5(1.85)	0.8	1.02	8.5	1.85	1.20	8.5	
N2(0.95)	0.75	1.02	8.5	0.95	1.20	8.5	
N5(1.73)	0.75	1.02	8.5	1.73	1.20	8.5	
N6(1.22)	0.75	1.02	8.5	1.22	1.20	8.5	

Electrical:

Impedance: 50 ohm

Voltage Rating : \geq 500 V rms MIN. (depending on cable)

Insulator Resistance : $\geqq 5~G\Omega$

Dielectric Withstanding Voltage : 1000 V rms . Contact Resistance : Center Contact $\leqq 3 \text{ m}\Omega$. Outer Contact $\leqq 2.5 \text{ m}\Omega$.

Mechanical:

 $\begin{aligned} & Mating: 1/4-36 \ UNS \ Screw-on \ Coupling. \\ & Recommended \ Mating \ Torque: 7.1\sim 9.7 \ lbs \\ & Coupling \ Nut \ Retention \ Force: \ge 60.7 \ lbs \end{aligned}$

Environmental:

Temperature Range : -65°C to 165°C

Corrosion (Salt Spray): MIL-STD-202, Method 101, Cond. B Thermal Shock: MIL-STD-202, Method 107, Cond. B Mechanical: MIL-STD-202, Method 213, Cond. I Vibration: MIL-STD-202, Method 204, Cond. D Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

Scale NTS	Abbr. ST	Date 2019/07/08	Rev.	Proprietary Note This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws. This document or parts thereof, may not be used, disclosed	DWG.NO. S252	RoHS 2	
.X ±0 .XX ±0			s in mm	or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan. Customer P/N: Nil	TITLE SMA S/T Jack, End Launch Type		
Drawn Mark 2017/03/11	Ry	an G	Approved 5. Sua 5. 17/03/17	S-Conn Ent	erprise Co., Ltd.	S-CONN (S)	