

Electrical:

Voltage Rating : \geq 500 V rms MIN. (depending on cable)

Insulator Resistance : ${\,\geqq\,} 5~G\Omega$

Impedance: 50 ohm

Dielectric Withstanding Voltage : 1000 V rms . Contact Resistance : Center Contact \leqq 3 m Ω . Outer Contact \leqq 2.5 m Ω .

Cable	Dimensions				
Туре	A	В	C	D	
RG178	2.4	3.1	0.6	1.9	
1.37	2.4	3.1	0.6	1.4	
1.32	2.4	3.1	0.6	1.4	
1.13	2.4	3.1	1.1	1.2	
0.81	2.4	3.1	1.5	0.9	

Mechanical:

 $\begin{aligned} & Mating: 1/4-36 \ UNS \ Screw-on \ Coupling. \\ & Recommended \ Mating \ Torque: 7.1\sim 9.7 \ lbs \\ & Coupling \ Nut \ Retention \ Force: \ge 60.7 \ lbs \end{aligned}$

Environmental:

Temperature Range : -65°C to 165°C

Corrosion (Salt Spray): MIL-STD-202, Method 101, Cond. B Thermal Shock: MIL-STD-202, Method 107, Cond. B Mechanical: MIL-STD-202, Method 213, Cond. I Vibration: MIL-STD-202, Method 204, Cond. D

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

Scale NTS	Abbr. ST	Date 2019/07/08	Rev.	Proprietary Note This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws. This document or parts thereof, may not be used, disclosed	DWG.NO. S271	RoHS 2
		in mm	or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan. Customer P/N: Nil	TITLE SMA B/H-O Jack, Crimp Typ	oe	
Drawn **Mark** 2019 07 08	Ryo	rn G	pproved . San 09/07/08	S-Conn Ent	erprise Co., Ltd.	S-CONN [A'S-Cornet like World]