

| Cable Type | Dimensions | | | |
|-------------|------------|-----|------|-----|
| | A | B | C | D |
| RG174,316 | 1.65 | 2.7 | 0.6 | 3.2 |
| RG58 | 3.2 | 4.7 | 1.0 | 5.6 |
| Dacar 302 | 2.7 | 3.7 | 0.95 | 3.4 |
| RG6 | 4.9 | 6.5 | 1.2 | 7.5 |
| LMR200 | 3.2 | 4.6 | 1.2 | 5.6 |
| H155,LMR240 | 4.2 | 5.5 | 1.6 | 6.5 |

Electrical :


Impedance : 50 ohm

Mechanical :

Mating : M8x P0.75 Screw-on Coupling.

Notes :

1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
2. Any changes for interface dimensions are strictly prohibited.
3. The Material and plating are in various options per customer's request.
4. A complete information for connectors is available upon request.

| | | | | | | |
|---|------------|---|------|--|---------|---|
| Scale | Abbr. | Date | Rev. | Proprietary Note This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws. This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan. | DWG.NO. |  |
| NTS | ST | 2019/07/11 | B | | A201 | |
| Tolerances : .X ±0.2 .XX ±0.1 .XXX ±0.05 | |  All Dimensions in mm (Unless Otherwise Specified) | | Customer P/N: Nil | TITLE | FME S/T Jack, Crimp Type |
| Drawn | Checked | Approved | |  | | |
| Mark | Ryan | G. Sun | | | | |
| 2019/07/11 | 2019/07/11 | 2019/07/11 | | <p style="text-align: center;">S-Conn Enterprise Co., Ltd.</p> | | |