





Electrical:

Impedance: 50 ohm

Voltage Rating: 250 V rms MIN. (depending on cable)

Insulator Resistance : $\geq 1 \text{ G}\Omega$

Dielectric Withstanding Voltage: 750 V rms. Contact Resistance : Center Contact $\leq 5 \text{ m}\Omega$.

Outer Contact $\leq 2.5 \text{ m}\Omega$

Cable	Dimensions				
Туре	A	В	С	D	
RG174,316	1.7	2.7	0.6	3.2	

Mechanical:

Mating: #6-40 UNF Screw-on Coupling.

Environmental:

Temperature Range: -65°C to 165°C

Corrosion (Salt Spray): MIL-STD-202, Method 101,

Cond. B

Thermal Shock: MIL-STD-202, Method 107, Cond. B Mechanical: MIL-STD-202, Method 213, Cond. B

Vibration: MIL-STD-202, Method 204, Cond. D

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

Scale	Abbr.		Date		Rev.	
NTS	ST		2019/07/23		В	
$ \begin{array}{ll} \text{Tolerances:} \\ .X & \pm 0.2 \\ .XX & \pm 0.1 \\ .XXX & \pm 0.05 \end{array} $		$\oplus \Box$				
		All Dimensions in mm (Unless Otherwise Specified)				
Drawn		Checked		Approved		
Mark		Ryan		G.	Sun	
2017 03 17		2017 03 17		201	7/03/17	

Proprietary Note This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.

This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any

purpose, without the written permission of S-Conn, Taiwan. Customer P/N: Nil

DWG.NO.

SSC101



TITLE

SSMC S/T Plug, Crimp Type

S-Conn Enterprise Co., Ltd.

